



NOTES
 1-ALL RESISTORS IN OHMS UNLESS FOLLOWED BY K (1000) OR M (1000000).
 2-ALL RESISTORS 1/4 WATTS EXCEPT AS NOTED.
 3-ALL CAPACITORS IN MICROFARADS UNLESS FOLLOWED BY PF (PICOFARADS).
 4-ALL INDUCTORS IN MICROHENRIES UNLESS FOLLOWED BY MH (MILLIHENRIES) OR H (HENRIES).
 5-ALL VOLTAGES TAKEN WITH "0" SIGNAL.
 6-ALL P.C. BOARD GROUNDS RETURN TO CHASSIS GROUND.
 7-THIS UNIT HAS BEEN SPECIFICALLY DESIGNED TO ACCOMMODATE EUROPEAN STANDARD 50 MICRO SECOND DE EMPHASIS. THIS CAN BE ACCOMPLISHED BY REMOVING THREE CAPACITORS C411, C412, C902.

Q NO.	HK P/N.	2N NO.
Q302-Q303		
Q401-Q403		
Q501-Q504	43025972	SIMILAR TO 2N3417
Q802-Q805		
Q801		
Q101-Q106		
Q103-Q104		
Q304		
Q101-Q102	43027722	SIMILAR TO 2N5087
Q301	43028065	SIMILAR TO 2N2857
Q801	43028084	NONE
Q107-Q108	43028088	2N5458
Q109-Q110	43027872	BC239C