



PIN NO. VOLTAGE (V)			PIN NO. VOLTAGE (V)			PIN NO. VOLTAGE (V)		
IC101,103,104			IC105			IC301		
1	13.2	1	1	3.82	1	13.2	1	13.2
2	10.0	2	2	0	2	3.55	2	3.55
3	0	3	3	0.68	3	4.78	3	4.78
4	0	4	4	0	4	0.71	4	0.71
5	1.79	5	5	2.10	5	10.12	5	10.12
6	4.33	6	6	2.10	6	10.16	6	10.16
7	4.32	7	7	2.10	7	0	7	0
8		8	8	2.03	8	0.01	8	0.01
9		9	9	13.2	9	6.24	9	6.24
10		10	10	5.73	10	2.79	10	2.79
11		11	11	5.73	11	2.80	11	2.80
12		12	12	5.73	12	2.80	12	2.80
13		13	13	5.73	13	2.80	13	2.80
14		14	14	5.73	14	2.80	14	2.80
15		15	15	5.39	15	4.30	15	4.30
16		16	16	5.30	16	3.03	16	3.03
0		0	0		0		0	

- SCHEMATIC SYMBOLS:**
- Ⓜ POLYESTER FILM CAPACITOR
 - Ⓢ POLYSTYRENE FILM CAPACITOR
 - Ⓣ TANTALUM ELECTROLYTIC CAPACITOR
 - Ⓛ BIPOLAR CAPACITOR
 - NONFLAMMABLE RESISTOR

- NOTES:**
1. SCHEMATIC IS SUBJECT TO CHANGE WITHOUT NOTICE.
 2. RESISTANCE VALUES ARE IN OHMS. K = 1,000; M = 1,000,000
 3. CAPACITANCE VALUES 1.0 AND ABOVE ARE IN pF OR μF (P = pF, M = μF). LESS THAN 1.0 ARE IN μF. (ELECTROLYTIC CAPACITANCE VALUES ARE IN μF/MV.)
 4. VOLTAGES ARE MEASURED TO CHASSIS GROUND WITH A "DC VOLTMETER".

V : VOLTAGES MEASURED WITH NO SIGNAL APPLIED.