



ALL VOLTAGES MEASURED UNDER FOLLOWING CONDITIONS:
 1 - USE OF 11 MEGOHMS INPUT IMPEDANCE VTVM VOLTMETER.
 2 - ALL VOLTAGES ± 10% WITH RESPECT TO GROUND.
 3 - A.C. INPUT AT 117 V 50-60 CPS.
 4 - NO SIGNAL AT ANTENNA AND OTHER INPUT TERMINALS.
 5 - FRONT PANEL CONTROLS AT:
 MODE SELECTOR - MONO.
 VOLUME CONTROL - MAX.
 MUTING - OFF

UNLESS OTHERWISE SPECIFIED
 ALL RESISTORS 1/2 W 20%
 ALL CAPACITORS IN PF
 ALL INDUCTORS IN MICRO H
 FM. IF: 10.7 MC

SYMBOL NUMBERS NOT USED
 R 80 C 28
 R 87 C 33
 C 35

FOR SERIAL NUMBERS 22T04 AND ABOVE

MATERIAL	TITLE	PART NO.
	SCHEMATIC, MR 67	
FINISH	McIntosh LABORATORY INC.	USED ON:
	2 Chambers St. Binghamton, N. Y.	
TOLERANCES - unless otherwise specified	SCALE	DATE
± 1% Resistors ± 5% Inductors	VG	1, 4, 65
± 0.05% Capacitors	CB	APR 3 1965
		SC123-176